

TOYOTA CELICA / MR2

3sgte



CAMSHAFTS

DESCRIPTION	CAM #	ADV DURATION	DUR @ .050"	LIFT (inches)	LIFT (mm)	KIT #	TIMING EVENTS	
STAGE 2 Street/Strip Specification Plug and play application. Short duration for nice street manners, slight lobe at idle. Excellent all purpose spec. OEM spring OK.	BC0351	264°/264°	216°/216°	.344"/.344"	8.74/8.74	BC0600	-	-
							BTDC	ATDC
							-	-
							ABDC	BBDC
STAGE 3 Race Specification Longer duration profile, added rpm potential. Intended for fully built engine. Tuning and ECU mods recommended. Requires shim under bucket.	BC0352	272°/272°	222°/222°	.400"/.400"	10.16/10.16	BC1600	-	-
							BTDC	ATDC
							-	-
							ABDC	BBDC
USDM 3SGTE (MR2)	Stock	248°/248°	204°/204°	.335"/.335"	8.51/8.51			



VALVE SPRING/RETAINER KIT

Designed for high rpm, BC valve springs are wound from only the highest grade, super clean, chrome silicone alloy and feature proprietary processing procedures for consistent pressures. BC retainers and spring seats are CNC machined from 6AL4V titanium to exacting tolerances.

KIT #	SPRING #	RETAINER #	DESCRIPTION
BC0600	BC1600	BC2300-16	Single spring, titanium retainer

Spring Pressure:
BC1600